

## C13

### PROFILE

Centerm C13, with slim and fashion design, featured by latest COSA innovative UI , brings you into the cloud world with extremely low cost.


### FEATURES

- **Innovative UI**  
Simple, neat and user-friendly UI.
- **Multiple VDI Support**  
Supports Microsoft RDP, Citrix ICA and VMware (RDP) protocols and offers smooth user experience
- **Low power consumption**  
A green product with less than 3.3w power consumption and low CO2 emission
- **Convenient Management**  
Supports centralized management with Centerm CCCM management software
- **Compact, Flexible & secure**  
Small size, fan-less design, VESA mountable, anti-theft Kensington slot.




### Connectivity

1. Power Button
2. USB 2.0 port
3. USB 2.0 port
4. VGA port
5. 10/100Mbps Ethernet



1. Kensington slot
2. Audio Output
3. Audio Mic In
4. USB 2.0 port
5. USB 2.0 port
6. Power Jack



## SPECIFICATION

| SYSTEM                     |  |
|----------------------------|--|
| Processor                  | ARM Cortex A9  |
| Available Operating System | COSA ①   |
| VDI/HSD Support            | Citrix Receiver / VMware view / Microsoft RDP 8 Compatible |
| Management                 | CCCM   |
| MEMORY                     |  |
| RAM (DDR3)                 | 512MB  |
| Storage (ROM)              | 4G EMMC  |
| DISPLAY                    |  |
| Port                       | VGA x 1 ( optional HDMI port)                              |
| Resolution                 | VGA up to 1920x1200@60Hz                                   |
| Color Depth                | support 24bit true color                                   |
| Dual Display               | Supported  |
| Network                    |  |
| LAN                        | x1 (10/100Mbps Base-T Fast Ethernet, RJ-45)                |
| WLAN                       | - (optional) internal USB WIFI module ②                    |
| I/O PERIPHERAL INTERFACE   |  |
| USB 2.0                    | x2 (front), x2 (side)                                      |
| RJ-45                      | x 1  |
| AUDIO                      |  |
| Line-out                   | x1 (1/8-inch mini-jack, 16-bit stereo)                     |
| Mic-in                     | x1(1/8-inch mini-jack, 16-bit stereo microphone)           |
| DIMENSION                  |  |
| Device                     | 93.5mm x 93.5mm x 20.4mm                                   |
| Packaging                  | 212mm x 135mm x 58mm                                       |
| Net Weight                 | 0.2 kg   |
| Power                      |  |
| Adapter                    | Worldwide auto-sensing 100-240V AC, 50/60 Hz, 5V/3A DC     |
| Power Consumption          | < 3.3w   |
| ENVIRONMENT                |  |
| Cooling                    | Fan-less Convection  |
| Operation Temperature      | 0°C to 40°C  |
| Relative Humidity          | 30% to 90% non-condensing                                  |

①: Centerm Operating System (Linux) for ARM platform

②: The case shall be reformed for antenna port. Please specify before order.

## Centerm Information Co. , Ltd (China)

Add: 2F,#22 Star-net Scient Plaza,Juyuanzhou,#618 Jinshan Road,  
Fuzhou, Fujian, China 350002 Tel: +86-591-28053888 ext 8757

## Centerm Information APAC (Singapore)

Add: 18 Kaki Bukit Road 3,Entrepreneur Business Centre, # 04-12,  
Singapore 415978 Tel:+65 9015 1946